

SILVER 20 EXT

Performance Data

| | |
|----------------------------------|------|
| Total Solar Energy Rejected | 82% |
| Solar Energy Reflected | 67% |
| Solar Energy Absorbed | 20% |
| Solar Energy Transmitted | 13% |
| Visible Light Transmitted | 16% |
| Visible Light Reflected | 62% |
| Ultra Violet Light Rejected | 99% |
| Shading Coefficient | 0.21 |
| Solar Heat Gain Coeff. (g Value) | 0.18 |
| Emissivity | 0.73 |
| Glare Reduction | 82% |

Performance Guide

| | |
|----------------------|-------------------------------------|
| Solar Heat Rejection | ★★★★★ |
| Glare Reduction | ★★★★★ |
| UV Reduction | ★★★★★ |
| Fade Reduction | ★★★★★ |
| Safety & Security | ☆☆☆☆☆ |
| One-Way Privacy | ★★★★☆ |
| Two-Way Privacy | ☆☆☆☆☆ |
| Scratch Coating | Yes |
| Warranty Period | 3 Years Vertical 2 Years Sloping |

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Excellent performing external Silver with up to 3 years warranty. Matches Silver 20 in appearance. Edge sealant needed for warranty compliance. All sloped projects please contact your supplier for further details of warranty period.

Please refer to your supplier for explanations on performance data, performance guide and application restrictions.

