

SILVER 20 XTRA EXT

Performance Data

Total Solar Energy Rejected	82%
Solar Energy Reflected	67%
Solar Energy Absorbed	21%
Solar Energy Transmitted	12%
Visible Light Transmitted	16%
Visible Light Reflected	64%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.20
Solar Heat Gain Coeff. (g Value)	0.17
Emissivity	0.73
Glare Reduction	82%

Performance Guide

Solar Heat Rejection	★★★★★
Glare Reduction	★★★★★
UV Reduction	★★★★★
Fade Reduction	★★★★★
Safety & Security	☆☆☆☆☆
One-Way Privacy	★★★★☆
Two-Way Privacy	☆☆☆☆☆
Scratch Coating	Yes
Warranty Period	7 Years Vertical 4 Years Sloping

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Excellent performing 2nd generation external Silver with up to 7 years warranty. Matches Silver 20 in appearance. Ideal where internal grade film prohibited. Edge sealant needed for warranty compliance. All sloped projects please contact your supplier for further details of warranty period.

Please refer to front pages for explanations on performance data, performance guide and application restrictions.

