

SILVER 35 EXT

Performance Data

Total Solar Energy Rejected	64%
Solar Energy Reflected	39%
Solar Energy Absorbed	35%
Solar Energy Transmitted	26%
Visible Light Transmitted	36%
Visible Light Reflected	36%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.41
Solar Heat Gain Coeff. (g Value)	0.35
Emissivity	0.72
Glare Reduction	59%

Performance Guide

Solar Heat Rejection	★ ★ ★ ★ ☆
Glare Reduction	★ ★ ★ ★ ☆
UV Reduction	★ ★ ★ ★ ★
Fade Reduction	★ ★ ★ ★ ★
Safety & Security	☆ ☆ ☆ ☆ ☆
One-Way Privacy	★ ★ ★ ★ ☆
Two-Way Privacy	☆ ☆ ☆ ☆ ☆
Scratch Coating	Yes
Warranty Period	3 Years Vertical 2 Years Sloping

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Medium reflective Silver. Made to withstand the elements offering high performance heat and glare rejection. Up to 3 years warranty. Edge sealant needed for warranty compliance. All sloped projects please contact your supplier for further details of warranty period.

Please refer to your supplier for explanations on performance data, performance guide and application restrictions.

