

STAINLESS STEEL 35 EXT

Performance Data

Total Solar Energy Rejected	50%
Solar Energy Reflected	15%
Solar Energy Absorbed	49%
Solar Energy Transmitted	36%
Visible Light Transmitted	40%
Visible Light Reflected	16%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.58
Solar Heat Gain Coeff. (g Value)	0.50
Emissivity	0.85
Glare Reduction	55%

Performance Guide

Solar Heat Rejection	★ ★ ★ ★ ☆
Glare Reduction	★ ★ ★ ★ ☆
UV Reduction	★ ★ ★ ★ ★
Fade Reduction	★ ★ ★ ★ ☆
Safety & Security	☆ ☆ ☆ ☆ ☆
One-Way Privacy	★ ★ ★ ★ ☆
Two-Way Privacy	☆ ☆ ☆ ☆ ☆
Scratch Coating	Yes
Warranty Period	Up to 3 Years

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Discreet neutral appearance offering good light transmission. Edge sealant needed for warranty compliance. All sloped projects please contact your supplier for further details of warranty period.

Please refer to your supplier for explanations on performance data, performance guide and application restrictions.

