

# 4 MIL ANTI-GRAFFITI FOR PLASTICS

## Performance Data

Total Solar Energy Rejected	19%
Solar Energy Reflected	9%
Solar Energy Absorbed	14%
Solar Energy Transmitted	77%
Visible Light Transmitted	85%
Visible Light Reflected	11%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.93
Solar Heat Gain Coeff. (g Value)	0.96
Emissivity	-
Glare Reduction	3%

## Performance Guide

Solar Heat Rejection	☆☆☆☆☆
Glare Reduction	☆☆☆☆☆
UV Reduction	★★★★☆
Fade Reduction	★☆☆☆☆
Safety & Security	☆☆☆☆☆
One-Way Privacy	☆☆☆☆☆
Two-Way Privacy	☆☆☆☆☆
Scratch Coating	Yes
Warranty Period	2 years

Key: Excellent - ★★★★★ Some Benefit - ★★★☆☆ N/A - ☆☆☆☆☆

## Film Notes

Offers sacrificial barrier against paints, sprays and scratches. Suitable for most plastics and polycarbonate substrates. Removable without adhesive residue.

*Please refer to front pages for explanations on performance data, performance guide and application restrictions.*

