

COOLKOTE 60 EXT3

Performance Data

Total Solar Energy Rejected	82%
Visible Light Transmitted	17%
Visible Light Reflected	63%
Visible Light Absorbed	34%
Ultra Violet Block	99%
Total Solar Energy Reflected	67%
Total Solar Energy Transmitted	13%
Total Solar Energy Absorbed	20%
Shading Coefficient	0.21
Solar Heat Gain Coeff. (g-Value)	0.18
Glare Reduction	80%

Performance Guide

Solar Heat Rejection	★★★★★
Glare Reduction	★★★★★
UV Reduction	★★★★★
Fade Reduction	★★★★★
Safety & Security	☆☆☆☆☆
One-Way Privacy	★★★★☆
Two-Way Privacy	☆☆☆☆☆
Scratch Coating	Yes
Warranty Period	4 Years Vertical 3 Years Sloping

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Coolkote 60 Ext3 is an external solar control film with excellent heat and glare reduction that can be applied externally to polycarbonate, glass and most acrylic substrates. Not recommended for corrugated plastics and polyurethane. Coolkote 60 Ext3 requires a neutral silicone edge sealant on all 4 sides of the film. For further details please contact your supplier.

