

SILVER MATTE 20 XTRA EXTERNAL

Performance Data

Total Solar Energy Rejected	81%
Total Solar Energy Reflected	62%
Total Solar Energy Absorbed	28%
Total Solar Energy Transmitted	10%
Visible Light Transmitted	13%
Visible Light Reflected	48%
Ultra Violet Light Rejected	99.9%
Shading Coefficient	0.22
Solar Heat Gain Coeff. (g value)	0.19
Winter U Value	1.06
Emissivity	0.84
Glare Reduction	86%

Performance Guide

Solar Heat Rejection	★★★★★
Glare Reduction	★★★★★
UV Reduction	★★★★★
Fade Reduction	★★★★☆
Safety & Security	☆☆☆☆☆
One-Way Privacy	☆☆☆☆☆
Two-Way Privacy	★★★★★
Scratch Coating	Yes
Warranty Period	5 Years Vertical 3 Years Sloping

Key: Excellent - ★★★★★ Some Benefit - ★★★☆☆ N/A - ☆☆☆☆☆

Film Notes

Exterior application 24 hour privacy film. Great block out film. Extremely high heat rejection and glare control. Diffusive matte appearance from inside and mirror reflective when viewed externally. Edge sealant required. Ideal choice for Server and Stock rooms.

