

# NEUTRAL DN50

## Performance Data

Total Solar Energy Rejected	37%
Solar Energy Reflected	7.0%
Solar Energy Absorbed	42%
Solar Energy Transmitted	51%
Visible Light Transmitted	52%
Visible Light Reflected	8.0%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.73
Solar Heat Gain Coeff. (g Value)	0.63
Emissivity	0.88
Glare Reduction	41%

## Performance Guide

Solar Heat Rejection	★ ★ ☆ ☆ ☆
Glare Reduction	★ ☆ ☆ ☆ ☆
UV Reduction	★ ★ ★ ★ ★
Fade Reduction	★ ★ ☆ ☆ ☆
Safety & Security	☆ ☆ ☆ ☆ ☆
One-Way Privacy	☆ ☆ ☆ ☆ ☆
Two-Way Privacy	☆ ☆ ☆ ☆ ☆
Scratch Coating	Yes
Warranty Period	10 Years

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

## Film Notes

Two ply light neutral steel appearance with low reflectivity. Designed to minimise the exterior mirrored look, ideal for discreet, heritage projects both commercial and residential.

*Please refer to your supplier for explanations on performance data, performance guide and application restrictions.*