

Performance Data

Total Solar Energy Rejected	45%
Solar Energy Reflected	25%
Solar Energy Absorbed	28%
Solar Energy Transmitted	47%
Visible Light Transmitted	70%
Visible Light Reflected	21%
Ultra Violet Light Rejected	99%
Shading Coefficient	0.63
Solar Heat Gain Coeff. (g Value)	0.55
Emissivity	-
Glare Reduction	21%

Performance Guide

Solar Heat Rejection	★ ★ ★ ☆ ☆
Glare Reduction	☆ ☆ ☆ ☆ ☆
UV Reduction	★ ★ ★ ★ ★
Fade Reduction	★ ★ ★ ☆ ☆
Safety & Security	☆ ☆ ☆ ☆ ☆
One-Way Privacy	☆ ☆ ☆ ☆ ☆
Two-Way Privacy	☆ ☆ ☆ ☆ ☆
Scratch Coating	Yes
Warranty Period	10 Years

Key: Excellent - ★★★★★ Some Benefit - ★☆☆☆☆ N/A - ☆☆☆☆☆

Film Notes

Provides very effective heat and UV rejection yet allows good 2-way vision. Ideal for shop fronts and domestic applications.

Please refer to your supplier for explanations on performance data, performance guide and application restrictions.